







maxi orange

CONDENSATE REMOVAL PUMP

Need more performance? Designed for larger units, the Maxi Orange pump gives you the extra power when you need it.





35L/h max. flow



15m max. rec. head (flow rate 10L/h)



35dB(A)

KEY FEATURES

- High power motor
- Superior performance
- Submersible secondary reservoir included


SUITABILITY




- Up to 46kW / 157,000Btu/h
- High wall split systems; Ducted units;
 Floor standing & Chassis units

✓ Perfect for... Large commercial units








Maxi Orange

† Pump only

* Other voltages available



FP2210

18	٠.,						
10		٠.,					
16			1	5m max	. recom	mende	d head
0 14			·				
METRES HEAD 8 0			•	٠.			
ES 10							
ΛΕΤΕ 8				•	٠.		
² 6					·*·.		
4					٠,	٠	
2	230V						•••••
0	5	10	15 LITRE	20 S PER H	25 IOUR	30	35

Max. How	35L/n @ 0 nead			
Max. rec. head	15m			
Max. suction lift	2m			
Sound level@1m	35dB(A)			
Power supply	230V AC 50-60Hz 0.1A*			
Rated	Non continuous			
Class	II appliance 🔲			

MAXI ORANGE SPECIFICATIONS

2EI /b @ 0 bood

Max. unit output

Max. unit output

Max. water temp

Discharge tube

IP Protection

Safety switch

Max. water temp

46kW / 157,000Btu/h

46kW / 157,000Btu/h

IPX1

3.0A Normally closed

Description Part No.

1 Amp Fuse FP2620

Tube To Soil Stack Adaptor

Vinyl Tube Braided AX5100

MAXI ORANGE OPTIONS

Inline Filter 16mm

1/4" (6mm)



For more installation accessories take a look at our Aspen Xtra range

IN THE BOX

Maxi Orange pump • 1.5m Plug & play power cable • Reservoir • Reservoir lid with 1.5m sensor cable • Submersible reservoir • Anti siphon device • Float & filter • 1.5m Suction tube 6mm ID • 220mm Orange inlet hose 14mm ID • 150mm Vinyl breather tube 6mm ID • Drain connector kit • Fixing kit • Install manual

Download manual at aspenpumps.com

View install video at aspenpumps.com

Self priming

Thermal protection
Fully potted









